

Safety Data Sheet

GHS Compliant

Printing date 05.19.2016




Revision: 05.19.2016

1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Touch n' Foam Black Sealant
- **Article number:** EHS 9464
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Sealant
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Convenience Products, division of Clayton Corp.
866 Horan Drive
Fenton, MO 63026-2416
Phone: 636-349-5855
- **1.4 Emergency telephone number:**
ChemTel Inc.
(800)255-3924, +1 (813)248-0585



2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412.
May displace oxygen and cause rapid suffocation. (USA GHS Only)
-  gas cylinder
 Press. Gas H280 Contains gas under pressure; may explode if heated.
-  health hazard
 Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 Carc. 2 H351 Suspected of causing cancer.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
- 

 Acute Tox. 4 H332 Harmful if inhaled.
 Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2 H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H335 May cause respiratory irritation.
- Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Safety Data Sheet

GHS Compliant


Printing date 05.19.2016

Revision: 05.19.2016


Trade name: Touch n' Foam Black Sealant

(Contd. of page 1)


- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

-  Xn; Harmful

- R20-40: Harmful by inhalation. Limited evidence of a carcinogenic effect.

-  Xn; Sensitising

- R42/43: May cause sensitisation by inhalation and skin contact.

-  Xi; Irritant

- R36/37/38: Irritating to eyes, respiratory system and skin.

- R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H229, H412.

The product is classified and labelled according to the CLP regulation.

- **Hazard pictograms**



GHS04 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labelling:**

diphenylmethanediisocyanate, isomeres and homologues

tris[2-chloro-1-(chloromethyl)ethyl] phosphate

4,4'-methylenediphenyl diisocyanate

trans-dichloroethylene

- **Hazard statements**

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412.

May displace oxygen and cause rapid suffocation. (USA GHS Only)

H280 Contains gas under pressure; may explode if heated.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Contd. on page 3)

Safety Data Sheet

GHS Compliant

Printing date 05.19.2016

Revision: 05.19.2016

Trade name: Touch n' Foam Black Sealant

(Contd. of page 2)

H317 May cause an allergic skin reaction.
 H351 Suspected of causing cancer.
 H335 May cause respiratory irritation.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P285 In case of inadequate ventilation wear respiratory protection.
 P281 Use personal protective equipment as required.
 P202 Do not handle until all safety precautions have been read and understood.
 P260 Do not breathe mist/vapours/spray.
 P314 Get medical advice/attention if you feel unwell.
 P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.


· **Additional information:**

Contains isocyanates. May produce an allergic reaction.
 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
 3,3 % by mass of the contents are flammable

· **Hazard description:**

· **WHMIS-symbols:**

A - Compressed gas
 D2A - Very toxic material causing other toxic effects



· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



* - Indicates a long term health hazard from repeated or prolonged exposures.

· **HMIS Long Term Health Hazard Substances**

9016-87-9	diphenylmethanediisocyanate, isomeres and homologues
101-68-8	4,4'-methylenediphenyl diisocyanate

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 4)

Safety Data Sheet

GHS Compliant

Printing date 05.19.2016

Revision: 05.19.2016

Trade name: **Touch n' Foam Black Sealant**

(Contd. of page 3)

3 Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 9016-87-9	diphenylmethanediisocyanate, isomers and homologues ☒ Xn R20; ☒ Xn R42/43; ☒ Xi R36/37/38 Carc. Cat. 3	20-40%
	☠ Resp. Sens. 1, H334; STOT RE 2, H373 ☠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 811-97-2 EINECS: 212-377-0	Norflurane	10-20%
	⚠ Press. Gas, H280	
CAS: 101-68-8 EINECS: 202-966-0 Index number: 615-005-00-9	4,4'-methylenediphenyl diisocyanate ☒ Xn R20; ☒ Xn R42/43; ☒ Xi R36/37/38 Carc. Cat. 3	10-20%
	☠ Resp. Sens. 1, H334; STOT RE 2, H373 ☠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 13674-84-5	tris(2-chlorisopropyl)-phosphate R52/53	10-20%
	Aquatic Chronic 3, H412	
CAS: 13674-87-8 EINECS: 237-159-2 Index number: 015-199-00-X	tris[2-chloro-1-(chloromethyl)ethyl] phosphate ☒ Xn R40; ☠ N R51/53	5-10%
	☠ Carc. 2, H351 ☠ Aquatic Chronic 2, H411	
CAS: 156-60-5 EINECS: 205-860-2 Index number: 602-026-00-3	trans-dichloroethylene ☒ Xn R20; ☠ F R11 R52/53	1-5%
	☠ Flam. Liq. 2, H225 ☠ Acute Tox. 4, H332 Aquatic Chronic 3, H412	

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **4.1 Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

- **After inhalation:**

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

(Contd. on page 5)

Safety Data Sheet

GHS Compliant

Printing date 05.19.2016

Revision: 05.19.2016

Trade name: Touch n' Foam Black Sealant

(Contd. of page 4)

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

Do not pull solidified product off the skin.

If skin irritation continues, consult a doctor.

- **After eye contact:**

Immediately remove contact lenses if possible.

Rinse opened eye for several minutes under running water. Then consult a doctor.

- **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

- **4.2 Most important symptoms and effects, both acute and delayed**

Asthma attacks

Headache

Breathing difficulty

Allergic reactions

Coughing

Nausea

Gastric or intestinal disorders when ingested.

Irritant to skin and mucous membranes.

Irritant to eyes.

Dizziness

Disorientation

- **Hazards**

Danger of impaired breathing.

Danger of disturbed cardiac rhythm.

Danger of pneumonia.

Danger of pulmonary oedema.

Danger of convulsion.

- **4.3 Indication of any immediate medical attention and special treatment needed**

Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

In cases of irritation to the lungs, initial treatment with cortical steroid inhalants.

Monitor circulation.

If necessary oxygen respiration treatment.

Medical supervision for at least 48 hours.

Contains isocyanates. May produce an allergic reaction.

5 Firefighting measures

- **5.1 Extinguishing media**

- **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Water in flooding quantities.

- **For safety reasons unsuitable extinguishing agents:** None.

- **5.2 Special hazards arising from the substance or mixture**

Danger of receptacles bursting because of high vapour pressure when heated.

During heating or in case of fire poisonous gases are produced.

(Contd. on page 6)

Safety Data Sheet

GHS Compliant

Printing date 05.19.2016

Revision: 05.19.2016

Trade name: Touch n' Foam Black Sealant

(Contd. of page 5)

- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information** Cool endangered receptacles with water spray.

6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Protect from heat.
Isolate area and prevent access.
Keep people at a distance and stay on the windward side.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Allow to solidify. Pick up mechanically.
Send for recovery or disposal in suitable receptacles.
Dispose contaminated material as waste according to item 13.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **7.1 Precautions for safe handling**
Keep away from heat and direct sunlight.
Use only in well ventilated areas.
- **Information about fire - and explosion protection:**
Keep respiratory protective device available.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray onto a naked flame or any incandescent material.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
Provide ventilation for receptacles.
Avoid storage near extreme heat, ignition sources or open flame.
- **Information about storage in one common storage facility:**
Store away from foodstuffs.
Store away from oxidizing agents.

(Contd. on page 7)

Safety Data Sheet

GHS Compliant

Printing date 05.19.2016

Revision: 05.19.2016

Trade name: Touch n' Foam Black Sealant

(Contd. of page 6)

- **Further information about storage conditions:**
Protect from heat and direct sunlight.
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.
- **7.3 Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

Ingredients with limit values that require monitoring at the workplace:

811-97-2 Norflurane

WEEL (USA) Long-term value: 1000 ppm

101-68-8 4,4'-methylenediphenyl diisocyanate

PEL (USA) Ceiling limit: 0,2 mg/m³, 0,02 ppm

REL (USA) Long-term value: 0,05 mg/m³, 0,005 ppm
Ceiling limit: 0,2* mg/m³, 0,02* ppm
*10-min

TLV (USA) Long-term value: 0,051 mg/m³, 0,005 ppm

EL (Canada) Short-term value: C 0,01 ppm
Long-term value: 0,005 ppm
Skin; S

EV (Canada) Long-term value: 0,005 ppm

156-60-5 trans-dichloroethylene

PEL (USA) Long-term value: 790 mg/m³, 200 ppm

REL (USA) Long-term value: 790 mg/m³, 200 ppm

TLV (USA) Long-term value: 793 mg/m³, 200 ppm

EL (Canada) Long-term value: 200 ppm

EV (Canada) Short-term value: 990 mg/m³, 250 ppm
Long-term value: 790 mg/m³, 200 ppm

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.
- **Additional information:** The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
Clean skin thoroughly immediately after handling the product.

(Contd. on page 8)

Safety Data Sheet

GHS Compliant

Printing date 05.19.2016

Revision: 05.19.2016

Trade name: **Touch n' Foam Black Sealant**

(Contd. of page 7)

- **Respiratory protection:**



Combined Organic Vapor and Particulate Respirator is recommended for use during all processing activities.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Safety glasses

- **Body protection:** Protective work clothing

- **Limitation and supervision of exposure into the environment**

No further relevant information available.

- **Risk management measures**

See Section 7 for additional information.

No further relevant information available.

9 Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:

Aerosolized liquid with compressed gas in cylinders

Colour:

Amber coloured

- **Odour:**

Light

Petroleum-like

- **Odour threshold:**

Not determined.

- **pH-value:**

Not determined.

- **Change in condition**

Melting point/Melting range:

Not Determined.

(Contd. on page 9)

Safety Data Sheet

GHS Compliant

Printing date 05.19.2016

Revision: 05.19.2016

Trade name: Touch n' Foam Black Sealant

(Contd. of page 8)

<p>Boiling point/Boiling range:</p> <ul style="list-style-type: none"> · Flash point: · Flammability (solid, gaseous): · Auto/Self-ignition temperature: · Decomposition temperature: · Self-igniting: · Danger of explosion: · Explosion limits: <ul style="list-style-type: none"> Lower: Upper: · Vapour pressure: · Density at 20 °C: · Relative density · Vapour density · Evaporation rate · Solubility in / Miscibility with water: · Partition coefficient (n-octanol/water): · Viscosity: <ul style="list-style-type: none"> Dynamic: Kinematic: · Solvent content: <ul style="list-style-type: none"> VOC (US EPA Method 24) · 9.2 Other information 	<p>-15 °F / -26 °C</p> <p>Not applicable, as aerosol.</p> <p>Not applicable.</p> <p>Not determined.</p> <p>Not determined.</p> <p>Product is not self-igniting.</p> <p>Product is not explosive. However, formation of explosive air/vapour mixtures are possible.</p> <p>Not determined.</p> <p>Not determined.</p> <p>Not determined.</p> <p>1,02 g/cm³</p> <p>Not determined.</p> <p>Not determined.</p> <p>Not applicable.</p> <p>Not miscible or difficult to mix.</p> <p>Not determined.</p> <p>Not determined.</p> <p>Not determined.</p> <p>0 g/l</p> <p>No further relevant information available.</p>
--	--

10 Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
Develops readily flammable gases/fumes.
Reacts with oxidizing agents.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.
Contact with acids releases toxic gases.
Danger of receptacles bursting because of high vapour pressure when heated.
- **10.4 Conditions to avoid**
Keep ignition sources away - Do not smoke.

(Contd. on page 10)

Safety Data Sheet

GHS Compliant

Printing date 05.19.2016

Revision: 05.19.2016

Trade name: Touch n' Foam Black Sealant

(Contd. of page 9)

Store away from oxidizing agents.

- **10.5 Incompatible materials:** No further relevant information available.

- **10.6 Hazardous decomposition products:**

Carbon monoxide and carbon dioxide

Nitrogen oxides (NO_x)

Hydrogen cyanide (prussic acid)

Phosphorus oxides (e.g. P₂O₅)

Chlorine

11 Toxicological information

- **11.1 Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral	LD50	2200 mg/kg (mouse)
------	------	--------------------

13674-87-8 tris[2-chloro-1-(chloromethyl)ethyl] phosphate

Oral	LD50	>2000 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>2000 mg/kg (rabbit)
--------	------	----------------------

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Irritating effect.

- **Sensitization:**

Sensitization possible through inhalation.

Sensitization possible through skin contact.

- **Subacute to chronic toxicity:**

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

Danger through skin adsorption.

Toxic and/or corrosive effects may be delayed up to 24 hours.

Suspected of causing cancer.

In addition to local irritant manifestations, there is a narcotic effect when inhaling high concentrations, with the danger of central respiratory arrest.

Asphyxiant gas.

- **Acute effects (acute toxicity, irritation and corrosivity):** Vapours have narcotic effect.

- **Repeated dose toxicity:**

May cause damage to organs through prolonged or repeated exposure.

Repeated exposures may result in skin and/or respiratory sensitivity.

(Contd. on page 11)

Safety Data Sheet

GHS Compliant

Printing date 05.19.2016

Revision: 05.19.2016

Trade name: Touch n' Foam Black Sealant

(Contd. of page 10)

- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**
Carc. 2

12 Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:**
The product contains materials that are harmful to the environment.

13674-87-8 tris[2-chloro-1-(chloromethyl)ethyl] phosphate

LC50	1,1 mg/l (Oncorhynchus mykiss)
	96 h

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Avoid transfer into the environment.
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **14.1 UN-Number**
- **DOT, ADR, IMDG, IATA** UN3500

(Contd. on page 12)

Safety Data Sheet




GHS Compliant

Printing date 05.19.2016

Revision: 05.19.2016

Trade name: Touch n' Foam Black Sealant

(Contd. of page 11)

· 14.2 UN proper shipping name	
· DOT	Chemical under pressure, n.o.s. (Norflurane)
· ADR	3500 CHEMICAL UNDER PRESSURE, N.O.S. (Norflurane)
· IMDG, IATA	CHEMICAL UNDER PRESSURE, N.O.S. (Norflurane)
· 14.3 Transport hazard class(es)	
· DOT	
	
· Class	2.2
· Label	2.2
<hr/>	
· ADR	
	
· Class	2 8A Gases.
· Label	2.2
<hr/>	
· IMDG, IATA	
	
· Class	2.2
· Label	2.2
· 14.4 Packing group	
· DOT, ADR, IMDG, IATA	Not Regulated
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Gases.
· Danger code (Kemler):	20
· EMS Number:	F-C,S-V
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
<hr/>	
· ADR	
· Limited quantities (LQ)	0
· Transport category	3
· Tunnel restriction code	C/E
· UN "Model Regulation":	UN3500, CHEMICAL UNDER PRESSURE, N.O.S. (Norflurane), 2.2

(Contd. on page 13)

Safety Data Sheet

GHS Compliant

Printing date 05.19.2016

Revision: 05.19.2016

Trade name: Touch n' Foam Black Sealant

(Contd. of page 12)

15 Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

9016-87-9 diphenylmethanediisocyanate, isomers and homologues

101-68-8 4,4'-methylenediphenyl diisocyanate

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

- **Proposition 65 (California):**

- **Chemicals known to cause cancer:**

13674-87-8 tris[2-chloro-1-(chloromethyl)ethyl] phosphate

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic Categories**

- **EPA (Environmental Protection Agency)**

9016-87-9 diphenylmethanediisocyanate, isomers and homologues

CBD

101-68-8 4,4'-methylenediphenyl diisocyanate

D, CBD

156-60-5 trans-dichloroethylene

II

- **IARC (International Agency for Research on Cancer)**

9016-87-9 diphenylmethanediisocyanate, isomers and homologues

3

101-68-8 4,4'-methylenediphenyl diisocyanate

3

- **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **Canada**

- **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

- **Canadian Ingredient Disclosure list (limit 0.1%)**

101-68-8 4,4'-methylenediphenyl diisocyanate

(Contd. on page 14)

Safety Data Sheet GHS Compliant

Printing date 05.19.2016

Revision: 05.19.2016

Trade name: Touch n' Foam Black Sealant

(Contd. of page 13)

· **Canadian Ingredient Disclosure list (limit 1%)**

None of the ingredients is listed.

· **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- R11 Highly flammable.
- R20 Harmful by inhalation.
- R36/37/38 Irritating to eyes, respiratory system and skin.
- R40 Limited evidence of a carcinogenic effect.
- R42/43 May cause sensitisation by inhalation and skin contact.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 WHMIS: Workplace Hazardous Materials Information System (Canada)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)

(Contd. on page 15)

Safety Data Sheet

GHS Compliant

Printing date 05.19.2016

Revision: 05.19.2016

Trade name: Touch n' Foam Black Sealant

(Contd. of page 14)

LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
Press. Gas: Gases under pressure: Compressed gas
Press. Gas: Gases under pressure: Dissolved gas
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Carc. 2: Carcinogenicity, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

Sources

SDS Prepared by:
ChemTel Inc.
1305 North Florida Avenue
Tampa, Florida USA 33602-2902
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
Website: www.chemtelinc.com